



UWL REPOSITORY

repository.uwl.ac.uk

Advances in the assessment of mechanical properties of flexible pavements by
GPR

Benedetto, Andrea, Bianchini Ciampoli, Luca, Alani, Amir and Tosti, Fabio ORCID logo ORCID:
<https://orcid.org/0000-0003-0291-9937> (2019) Advances in the assessment of mechanical
properties of flexible pavements by GPR. In: EGU General Assembly 2019, 07-12 Apr 2019, Vienna,
Austria. (In Press)

This is the Accepted Version of the final output.

UWL repository link: <https://repository.uwl.ac.uk/id/eprint/5839/>

Alternative formats: If you require this document in an alternative format, please contact:
open.research@uwl.ac.uk

Copyright: Creative Commons: Attribution 4.0

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

Take down policy: If you believe that this document breaches copyright, please contact us at open.research@uwl.ac.uk providing details, and we will remove access to the work immediately and investigate your claim.

Rights Retention Statement:



Advances in the assessment of mechanical properties of flexible pavements by GPR

Andrea Benedetto (1), Luca Bianchini Ciampoli (1), Amir Morteza Alani (2), and Fabio Tosti (2)

(1) Roma Tre University, Department of Engineering, Rome, Italy (andrea.benedetto@uniroma3.it), (2) University of West London (UWL), School of Computing and Engineering, London, United Kingdom (Amir.Alani@uwl.ac.uk)

An extensive and time-efficient assessment of roads at the network level is crucial for road administrators and agencies to define priorities of intervention and decrease the likelihood of envisaged accidents.

Most of the damages in flexible pavements occur where stiffness of the asphalt and load-bearing layers is low. Therefore, an effective assessment of the strength and deformation properties of these layers can lead to identifying causes and locating the depth of damages. In addition, a prompt detection of early decay and loss of bearing capacity represents the real challenge to tackle for road administrators.

As a common practice in highway engineering, the Ground Penetrating Radar (GPR) and mechanical-based methods (e.g. Deflectometers, Curviameter, . . .) are used separately for the assessment of the geometric (i.e. evaluation of the layer thicknesses) and the strength and deformation properties (i.e. evaluation of the deflection bowl) of road flexible pavements, respectively. The integration of the above information allows to evaluate reliable values of stiffness modulus of the pavement layers. In view of the aforementioned limitations and state-of-the-art practices in the assessment of the mechanical properties of flexible pavements, the development of a non-destructive testing methodology for real-time identification of early decay and loss of bearing capacity of roads at traffic speed would stand as a step forward compared with the traditional methods. Value added would be to provide an estimation of the pavement stiffness based on geometric, physical and mechanical attributes of the subsurface integrated into a unique model. This would emphasise strengths and narrow weaknesses of the above NDTs.

In particular, this work proposes an experimental-based model for the assessment of the stiffness of a road flexible pavement using high frequency GPR and Curviameter non-destructive testing (NDT) methods. To this effect, a 12 km-long stretch of a rural road located in the District of Madrid, Spain, was subjected to both GPR and Curviameter surveys. The georeferencing of the tests allowed for the matching between the physical and mechanical information from the two devices. A section worth 5% of the total length of the inspected stretch was randomly selected for calibration purposes. The proposed predictive model takes as input physical properties of the pavement calculated by GPR (i.e. thickness of the bitumen-bound layers and rate of attenuation of the signal) and returns as output the overall bearing capacity of the pavement expressed through a dedicated parameter.

As an outcome, a promising potential of GPR system and mechanical-based NDTs for predicting bearing strength of flexible pavements is pointed out, proving this methodology to be worthy for implementation in pavement management systems (PMSs).